

TESTER, REMINDER AND CONTROLLER

TESTERS & MONITORS



A TETDS

Total Dissolved Solid Meter
TDS-3: 1 ~ 999PPM
TDS-2: 10 ~ 9990PPM



A TDS-D

Panel type TDS meter
Range: 1 ~ 9990 PPM



A TDS-D2

Industrial Water Quality Monitor
Source water reading:
1 ~ 1990 $\mu\text{s}/\text{cm}$ (1 ~ 1000 PPM)
RO water reading:
1 ~ 1990 $\mu\text{s}/\text{cm}$ (1 ~ 1000 PPM)



A TDS-S

Water quality test cup



A TESP001

Electrolysis Precipitator
110/220VAC



A PH-D

PH Reader



A PR-D

Digital Pressure Reader

AUTO FLUSHING CONTROLLER



A MC-2

Power: AC110V, 240V 50/60Hz
(24V available)
* Six indicator lamps
* Manual flush button

WATER FLOW COUNTER



A BVMW

Mechanical Type Flow Counter
8000liter(2000gal.) shut-off



A DF-6000

Digit Flow Monitor
Monitor up to 5 liters

LABORATORY TESTERS



A EC-410

Microprocessor Water
Quality Monitor
Resistivity: Range:
0.00M Ω .cm~20.00 M Ω .cm
Conductivity Range:
0.00 $\mu\text{s}/\text{cm}$ ~200.0 $\mu\text{s}/\text{cm}$
Temperature:
0~100°C



A TS-1

Portable pH/ORP METER
Range: pH: 0.00~14Ph
mV: -1999~+1999mV



A CM-230

Conductivity Monitor
Conductivity Range:
0.00 $\mu\text{s}/\text{cm}$ ~2000 $\mu\text{s}/\text{cm}$