

Compact Types



ARO-150G



ARO-150G-N

20" 5 micron Prefilter
20" 1 micron Prefilter
20" Carbon block Prefilter
Anti-Scalent Prefilter
Booster Pump & Transformer
TFC R.O. membranes(75gpd*2)
Post Granular Carbon filter
High/Low Pressure Switch
Auto Shut-off Valve
Flow Restrictor
Faucet & Installation kit
Auto Flush Controller(option)
Solenoid Valve 3/8", 1/4"
Shipping Dimension & weight:
48x26x83cm 20kgs



ARO-200G

ARO-200G-N



ARO-300G

ARO-300G-N

20" 5 micron Prefilter
20" 1 micron Prefilter
20" Carbon block Prefilter
Anti-Scalent Prefilter
Booster Pump & Transformer * 2 sets *3 sets
TFC R.O. membranes(100gpd*2, *3)
Post Granular Carbon filter
High/Low Pressure Switch
Faucet & Installation kit
Auto Flush Controller(option)
Solenoid Valve 3/8", 1/4"
Shipping Dimension & weight:
48x32x83cm 28kgs (ARO-200G)
48x32x83cm 28.3kgs (ARO-300G)



ARO-400G



ARO-400G-N

20" 5 micron Prefilter
20" 1 micron Prefilter
20" Carbon block Prefilter
Anti-Scalent Prefilter
Booster Pump & Transformer * 4 sets
TFC R.O. membranes(100gpd*4)
Post Granular Carbon filter
High/Low Pressure Switch
Faucet & Installation kit
Auto Flush Controller(option)
Solenoid Valve 3/8", 1/4"
Shipping Dimension & weight:
48x32x83cm 29kgs

Commercial Types

VERTICAL TYPE



ARO-300G-2



ARO-600G-2

S.steel frame
20" Prefilters x 3
S.steel Membrane vessel (*2)
2.5" x 21" membrane (*2)
Inlet & Flush Solenoid Valve
Source & Ro Gauge
Inlet & Concentration Flow meter
125gph vane pump & 1/2hp motor
Auto Flush Controller
Pressure Regulator
Anti-scalent device
Electricity consumption: 392W
Shipping Dimension & weight:
48x60x72cm 35kgs (300G-2)
48x60x72cm 36kgs (600G-2)



ARO-800G

S.steel frame
20" Prefilters x 3
S.steel Membrane vessel
4" x 21" membrane
Inlet & Flush Solenoid Valve
Source & Ro Gauge
Inlet & Concentration Flow meter
240gph vane pump & 1hp motor
Auto Flush Controller
TDS detector
Pressure Regulator
Anti-scalent device
Electricity consumption: 764W
Shipping Dimension & weight:
80x50x116cm 60kgs



ARO-1500G up to 2000G

S.steel frame
20" Prefilters x 3
Fiber Glass Membrane vessel
4" x 40" membrane
Inlet & Flush Solenoid Valve
Source & Ro Gauge
Inlet & Concentration Flow meter
240gph vane pump & 1hp motor
Auto Flush Controller
TDS detector
Pressure Regulator
Anti-scalent device
Electricity consumption: 764W
Shipping Dimension & weight:
80x50x145cm 65kgs

