

3000gpd to 10000gpd



ARO-3000G up to 4000G

S.steel frame
20" Prefilters x 3
Fiber Glass Membrane vessel*2
4" x 40" membrane*2
Inlet Actuator & Flush Solenoid Valve
Source & Ro Gauge
Inlet & Concentration Flow meter
S.steel Vertical Pump 1.1kW
(single phase motor)
Auto Flush Controller
TDS detector
Pressure Regulator
Gate Valve
Anti-sclent device*1
Electricity consumption: 1120W
Shipping Dimension & weight:
80x50x145cm 78kgs

ARO-4500G up to 5500G

S.steel frame
20" Prefilters x 3
Fiber Glass Membrane vessel*3
4" x 40" membrane*3
Inlet Actuator & Flush Solenoid Valve
Source & Ro Gauge
Inlet & Concentration Flow meter
S.steel Vertical Pump 2.2kW
(single phase motor)
Auto Flush Controller
TDS detector
Pressure Regulator
Gate Valve
Anti-sclent device*2
Electricity consumption: 2220W
Shipping Dimension & weight:
80x50x145cm 88kgs

ARO-6000G up to 8000G

S.steel frame
Fiber Glass Membrane vessel*4
4" x 40" membrane*4
Inlet Actuator & Flush Solenoid Valve
Source & Ro Gauge
Inlet & Concentration Flow meter
S.steel Vertical Pump 2.2kW
(single phase motor)
Auto Flush Controller
TDS detector
Accumulated timer
Pressure Regulator
Gate Valve
Anti-sclent device*2
Electricity consumption: 2220W
Shipping Dimension & weight:
80x50x145cm 88kgs

ARO-10000G up to 12000G

S.steel frame
Fiber Glass Membrane vessel*6
4" x 40" membrane*6
Inlet & Flush Solenoid Valve
Source & Ro Gauge
Inlet & Concentration Flow meter
S.steel Vertical Pump 4.0kW
(three phase motor)
Auto Flush Controller
TDS detector
Accumulated timer
Pressure Regulator
Gate Valve
Anti-sclent device*3
Electricity consumption: 4020W
Shipping Dimension & weight:
112x101x150cm 120kgs



14000gpd & Water Station Type



ARO-14000G up to 16000G

S.steel frame
Fiber Glass Membrane vessel*8
4" x 40" membrane*8
Inlet Actuator & Flush Solenoid Valve
Source & Ro Gauge
Inlet & Concentration Flow meter
S.steel Vertical Pump 4.0kW
(three phase motor)
Auto Flush Controller
TDS detector
Accumulated timer
Pressure Regulator
Gate Valve
Anti-sclent device*4
Electricity consumption: 4020W
Shipping Dimension & weight:
112x101x150cm

The leading brand of RO Element



RO ELEMENT NSF approved RO Elecmnt,
Low pressure, high flow, minimum rejection99%.
MBFT2521 MBAS2521: 300gpd @ 150psi
MBFT4021: 1000gpd @ 150psi
MBFT4040: 2200gpd @ 150psi

NON-STANDARD CHOICE

Through years' experiences, continuous effort in water treatment, we worked out different types of water facilities, cost, maintenance and environmental study, we concern more than clients.



WATER TREATMENT FACILITIES:

- Pump + Motor
- Cluster Filter
- Filtration System
- Dosing system
- Water Softener
- Reverse Osmosis Main Unit
- UV Sterilizer